

Clean copy of
claims 1, 2 and 4 - 10

Claims

1.(twice amended) A method for the stimulation and production of a hydrocarbon containing substance from a location below the surface of the earth, where said location is in fluid communication, via a well casing, with said surface, said method comprising the steps of

- 5 a.) positioning a transducer mechanism within said well casing at said location, said mechanism comprising a plurality of axially, spaced apart, circular transducer elements, where said transducer elements are electrically arranged in parallel and electrically excitable to produce a high energy, narrow, radiation pattern of high energy impulses extending
- 10 laterally from said well casing into said location;

b.) maintaining said transducer mechanism within an oil filled medium at a pressure essentially equal to the area in horizontal proximity to said mechanism; and,

c.) energizing said transducer mechanism.

2.(twice amended) The method according to claim 1, wherein said high energy, radiation pattern is horizontally focused within a circular band of between 2 and 3 degrees.

C ~~3~~ *A* (amended) The method according to claim ~~2~~, wherein said transducer elements are sealed within a pressure controlled housing.

B3 ~~4~~ *A* (amended) The method according to claim 1, wherein said transducer mechanism is energized at a frequency of at least 20 kHz.

⁵~~6~~.(amedned) The method according to claim 1, wherein said well casing includes a series of through holes at said location to facilitate movement of said hydrocarbon containing substance into said well casing.

⁶~~7~~.(amended) The method according to claim ¹~~3~~, wherein each said transducer element is a piezoelectric substance.

⁷~~8~~.(amedned) The method according to claim ⁶~~7~~, wherein said piezoelectric substance is a ceramic.

⁸~~9~~.(amended) The method according to claim ⁸⁷~~8~~, wherein said transducer mechanism is energized at a frequency of at least 20kHz.

⁹~~10~~.(amended) The method according to claim 1, wherein adjacent said plural transducer elements are spaced apart by dielectric spacer members.

15

B